

Rough Opening Schedule

SINGLE DOORS	config.*	width x height	DOUBLE DOORS	config.*	width x height
2/0 x 6/8	1	26-1/4" x 84"	(2) 2/0 x 6/8	8	51-1/2" x 84"
2/6 x 6/8	1	32-1/4" x 84"	(2) 2/6 x 6/8	8	63-1/2" x 84"
2/8 x 6/8	1	34-1/4" x 84"	(2) 2/8 x 6/8	8	67-1/2" x 84"
3-0 x 6/8	1	38-1/4" x 84"	(2) 3-0 x 6/8	8	75-1/2" x 84"
3/6 x 6/8	1	44-1/4" x 84"			
4/0 x 6/8	1	50-1/4" x 84"			

* Make openings for 8/0 doors 100" tall

* Make openings for 8/0 doors 100" tall

SIDELIGHT UNITS	configuration*	width x height
Single 3/0 x 6/8 with one 12" sidelight	2	52" x 84"
Single 3/0 x 6/8 with two 12" sidelights	3	65-1/2" x 84"
Single 3/0 x 6/8 with one 14" sidelight	2	54" x 84"
Single 3/0 x 6/8 with two 14" sidelights	3	69-1/2" x 84"

* Make openings for 8/0 doors 100" tall

TRANSOM UNITS	configuration*	height
6/8 units with 2 - 12" sidelites and a 12" rectangular transom	4	97-1/2"
6/8 units with 2 - 14" sidelites and a 14" rectangular transom	4	99-1/2"
8/0 units with 2 - 12" sidelites and a 12" rectangular transom	4	113-1/2"
8/0 units with 2 - 14" sidelites and a 14" rectangular transom	4	115-1/2"
6/8 units with 2 - 12" sidelites and a 19-3/8" segment transom	5	103-3/8"
6/8 units with 2 - 14" sidelites and a 20-1/2" segment transom	5	104-1/2"
8/0 units with 2 - 12" sidelites and a 19-3/8" segment transom	5	119-3/8"
8/0 units with 2 - 14" sidelites and a 20-1/2" segment transom	5	120-1/2"
6/8 units with 2 - 12" sidelites and a 17-1/4" elliptical transom	6	101-1/4"
6/8 units with 2 - 14" sidelites and a 19-1/4" elliptical transom	6	103-1/4"
8/0 units with 2 - 12" sidelites and a 17-1/4" elliptical transom	6	117-1/4"
8/0 units with 2 - 14" sidelites and a 19-1/4" elliptical transom	6	119-1/4"
6/8 units with 2 - 12" sidelites and a 31-1/2" half round transom	7	115-1/2"
6/8 units with 2 - 14" sidelites and a 33-1/2" half round transom	7	117-1/2"
8/0 units with 2 - 12" sidelites and a 31-1/2" half round transom	7	131-1/2"
8/0 units with 2 - 14" sidelites and a 33-1/2" half round transom	7	133-1/2"

***Door Unit Configurations - page 5.**

The rough opening dimensions were configured using Hoelscher prehung specifications.